

INVESTIGATION STUDY OF VARIOUS CARRIER TYPE FOR AIR TUNNEL  
TRANSPORTATION

WANIS MUSTAFA EDUKALI SHIBANI

A thesis submitted in  
fulfillment of the requirement for the award of the  
Doctor of Philosophy

Faculty of Mechanical and Manufacturing Engineering  
Universiti Tun Hussein Onn Malaysia

MAY 2018

specially dedicated to:

my Mother and my Wife,

Words cannot express everything you have done for me

Thank you for all of your love and support.

Brothers, sisters, friends and all those who have been  
a great help in the completion of this thesis.

My love for you all remains forever...



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## ACKNOWLEDGEMENT

I would like to take this opportunity to express this heartfelt appreciation to my respectful supervisor, Dr Mohd Fadhli bin Zulkafli for his supervision, encouragement, contradictive ideas, patience, guidance and invaluable advice, enabling me to achieve the objectives of this thesis.

I would also like to extend my appreciation to the man who had supported me at the beginning of my PhD journey, the late Professor Ir Dr Hj Abas Bin Ab Wahab. Many thanks to all the lecturers and technicians in UTHM, and especially to Ir Dr Bambang Basuno who have contributed their efforts and knowledge for the completion of this thesis.

Finally, I wouldn't have been in this position if I hadn't had the support and prayers from my family, especially my mother and my wife. I owe everything to them.



PERPUSTAKAAN TUNKU TUN AMINAH

## ABSTRACT

This study highlights the influences of internal airflow on the motion of carrier in an air tunnel. The aim of this work is to study an alternative method of transporting goods from one place to another through an air tunnel. The development of such transport system can help to reduce traffic jams and deliver goods faster to its desired places. The analysis of carrier movement and the flow surrounding it was performed using FLUENT software version 16.1. The computational domain along the air tunnel was discretized using tetrahedron grids. The adopted numerical scheme was the time-averaged Navier-Stokes equation with  $k - \varepsilon$  turbulence modeling and the scheme was solved using the SIMPLE algorithm. The air movement was created by the presence of pressure difference. The results indicate the possibility of defining a carrier, which has a particular geometry to float and move. This study was performed in three stages. The first stage started with the investigation of suitable geometry of the carrier. Four shapes were considered, i.e. box, ball, wedge A and wedge B shape. The wedge A and B had the same configurations and dimensions, but the only difference was the position of each shape, facing the inlet in the air tunnel. It was found that the wedge B and the box shape had the fastest speed compared to the other two shapes. Rectangular wings with a cross section of either FX63-137, NACA 0012 or NACA 4412 airfoil was selected for this study. In the second stage, a carrier in a box shape with three rectangular wings attached was investigated. In the last stage, the carrier in wedge B shape with wings attached was examined. The results indicate that the carrier equipped with the airfoil NACA0012 has better performance than the carrier that uses airfoil FX 63-137 or airfoil NACA 4412 at wind speed of 30.8 m/s. In the experimental testing, a carrier in a box shape with wings attached was assessed. The result reveals that the movement of the carrier (FX63-137) shows better performance at the wind speed of 19.6 m/s, and this result is consistent with the simulation result.

## ABSTRAK

Tujuan kajian ini adalah untuk mengkaji penggunaan terowong udara sebagai kaedah alternatif mengangkut barangan dan manusia dari satu tempat ke tempat yang lain. Pembangunan sistem pengangkutan seperti ini adalah penting kerana ia dapat membantu mengurangkan kesesakan lalu lintas dan pencemaran udara, selain dapat menghantar barangan ke tempat yang dituju dengan pantas. Pergerakan pengangkutan dan aliran sekeliling ketika ia sedang bergerak dianalisis menggunakan perisian FLUENT versi 16.1. Domain pengkomputeran terowong udara dibina menggunakan grid tetrahedron. Skim berangka yang digunakan ialah persamaan purata masa Navier-Stokes dengan permodelan pergolakan  $k - \epsilon$ . Skim ini diselesaikan menggunakan algoritma SIMPLE. Gerakan udara dibentuk melalui kehadiran perbezaan tekanan di antara keadaan aliran masuk dan keluar terowong udara. Kajian ini dijalankan di dalam tiga peringkat. Peringkat pertama melibatkan penyelidikan berkaitan geometri pengangkutan. Empat bentuk pengangkutan dikaji iaitu bentuk kiub, bola, baji A dan baji B. Dapatan kajian menunjukkan bentuk baji B dan kiub mempunyai kelajuan terpanjang berbanding bentuk bola dan baji A. Satu sayap berbentuk segiempat tepat yang mempunyai bahagian bersilang, dilengkapi samada dengan airfoil FX63-137, NACA 0012 atau NACA 4412, telah dipilih untuk kajian ini. Di peringkat kedua, pengangkutan berbentuk kiub yang dipasangkan tiga sayap berbentuk segi empat tepat telah dikaji. Di peringkat akhir, pengangkutan berbentuk baji B yang dipasangkan satu sayap berbentuk segi empat tepat telah dikaji. Hasil kajian menunjukkan pengangkutan yang dilengkapi dengan airfoil NACA0012 menunjukkan prestasi yang lebih baik berbanding pengangkutan yang dilengkapi dengan airfoil FX 63-137 atau airfoil NACA 4412 pada kelajuan angin 30.8 m/s. Di dalam eksperimen yang dijalankan, pengangkutan berbentuk kiub yang dipasangkan sayap berbentuk segi empat tepat diuji. Dapatan kajian menunjukkan pergerakan pengangkutan (FX63-137) adalah lebih baik pada kelajuan angin 19.6 m/s dan ini selaras dengan keputusan simulasi.

## CONTENTS

<b>TITLE</b>	<b>i</b>
<b>DECLARATION</b>	<b>ii</b>
<b>DEDICATION</b>	<b>iii</b>
<b>ACKNOWLEDGEMENT</b>	<b>iv</b>
<b>ABSTRACT</b>	<b>v</b>
<b>ABSTRAK</b>	<b>vi</b>
<b>CONTENTS</b>	<b>vii</b>
<b>LIST OF TABLES</b>	<b>xi</b>
<b>LIST OF FIGURES</b>	<b>xiii</b>
<b>LIST OF SYMBOLS AND ABBREVIATIONS</b>	<b>xxi</b>
<b>LIST OF APPENDICES</b>	<b>xxiv</b>
<b>LIST OF PUBLICATIONS</b>	<b>xxv</b>
<b>CHAPTER 1 INTRODUCTION</b>	<b>1</b>
1.1 Research Background	1
1.2 Problem Statement	2
1.3 Research Aim and Objectives	3
1.4 Research Scope	3
1.5 Research Outputs	4
1.6 Outline of the Thesis	4
<b>CHAPTER 2 LITERATURE REVIEW</b>	<b>5</b>
2.1 Introduction	5
2.2 Modern Transportation Using an Air Tunnel Concept	5
2.2.1 Pneumatic Air Tubes	5
2.2.1.1 Pneumatic Capsule Pipeline Transport for Hospitals	6
2.2.1.2 The Pneumatic Mail Tubes	8

2.2.1.3 Transport Cargoes in Capsules	10
2.2.1.4 The Difference Between the Japanese PCP Systems and the Pallet Tube PCP	12
2.2.1.5 Advantages and Disadvantages of Using the Pneumatic Capsule Pipeline System	12
2.2.2 The Magnetic Levitation (Maglev)	13
2.3 Flow in a pipe	14
2.3.1 Pitot Tube Tool	15
2.4 Computational Approach	17
2.4.1 Solution Method	17
2.4.2 Finite Volume Method	17
2.4.3 Turbulence Models	18
2.4.3.1 The Standard $k - \epsilon$ Turbulence Model	19
2.5 The Shape of the Carriers and the Air Tunnel	20
2.6 The Motion of the Carriers	28
2.7 Overview of the Ground Effect	30
2.8 Summary of the findings	31
<b>CHAPTER 3 METHODOLOGY</b>	<b>42</b>
3.1 Introduction	42
3.2 Computational Fluid Dynamic (CFD) Approach	42
3.3 Description of the Models	44
3.3.1 Shape of the Carrier	45
3.3.2 The Box with Wings Attached	47
3.3.3 The Scaled-Up Box with Wings Attached	49
3.3.4 The Wedge B with Wings Attached	51
3.4 Boundary Conditions	53
3.5 Meshing Topologies	54
3.5.1 Shape of the Carrier	55
3.5.2 Grid Independence Study	55
3.5.3 The Carrier with Wings Attached	55
3.5.4 The Wedge B with Wings Attached	57

3.6	The Domain and Boundary Condition of the Carriers for Studying Static Stability	57
3.7	Fluid Flow Governing Equations	59
3.8	Simulation Set-Up	59
3.8.1	Computational Time	60
3.9	Experimental Setup	60
3.9.1	Experimental Apparatus	62
3.9.1.1	Air Tunnel (Pipes)	62
3.9.1.2	Blower Pump	63
3.9.1.3	The Carriers	63
3.9.1.4	High-Speed Camera	64
3.9.2	Experiments procedure	65
3.9.3	Experiment Method	66
3.10	Chapter Summary	68
<b>CHAPTER 4 RESULTS AND DISCUSSIONS OF NUMERICAL ANALYSIS</b>		<b>69</b>
4.1	Introduction	69
4.2	Grid Independence Study for the Shape of the Carrier	69
4.2.1	The Motion of Carrier and Flow Pattern	72
4.3	Box with Wings Attached	77
4.3.1	The Optimum Initial Angle of Attack	77
4.3.2	The Carrier	78
4.3.3	The Scaled-Up Box with Wings Attached	88
4.3.3.1	Motion of the Carriers with Different Weights	102
4.3.4	The Movement of the Wedge B (NACA0012), and the Carrier (NACA0012) with Different Weights	104
4.3.4.1	Comparing the Results of the Wedge B (NACA0012), and the Carrier (NACA0012)	106
4.4	Summary	113



<b>CHAPTER 5 RESULTS OF EXPERIMENTS AND VALIDATION</b>	<b>115</b>
5.1 Introduction	115
5.2 Results and Discussion	115
5.2.1 The Carrier (FX63-137)	115
5.2.1.1 Static Stability Study of the Carrier (FX63-137)	132
5.2.2 The Carrier (NACA0012)	134
5.2.2.1 Static Stability Study of the Carrier (NACA0012)	148
5.2.3 The Carrier (NACA4412)	151
5.2.3.1 Static Stability Study of the Carrier (NACA4412)	165
5.3 Dimensional Analysis	168
<b>CHAPTER 6 CONCLUSIONS AND RECOMMENDATIONS</b>	<b>170</b>
6.1 Introduction	170
6.2 Conclusion	170
6.3 Contribution	171
6.4 Recommendations	171
<b>REFERENCES</b>	<b>172</b>
<b>APPENDICES</b>	<b>181</b>
<b>VITA</b>	<b>198</b>

## LIST OF TABLES

2.1	Summaries of related researchers work	32
3.1	Simulation settings of flow and movement of the carrier inside an air tunnel	60
4.1	The effect of grid size for grid independent study	72
4.2	The speed of models and the forces at the middle of the air tunnel	74
4.3	The results based on the distance covered by the carrier inside the air tunnel for the various high angles of attacks	78
4.4	The lift force of the wedge B (NACA0012) for some time steps (100grams)	106
4.5	The lift force of the carrier (NACA0012) for some time steps (100grams)	107
4.6	The lift force of the wedge B (NACA0012) for some time steps (200grams)	108
4.7	The lift force of the carrier (NACA0012) for some time steps (200grams)	108
4.8	The lift force of the wedge B (NACA0012) for some time steps (300grams)	109
4.9	The lift force of the carrier (NACA0012) for some time steps (300grams)	110
4.10	The lift force of the wedge B (NACA0012) for some time steps (400grams)	111
4.11	The lift force of the carrier (NACA0012) for some time steps (400grams)	111
4.12	The lift force of the wedge B (NACA0012) for	112

	some time steps (500grams)	
4.13	The lift force of the carrier (NACA0012) for some time steps (500grams)	113
5.1	Dimensions of variables used in the experiment	168



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## LIST OF FIGURES

2.1	Point to point system	6
2.2	Multipoint system	7
2.3	The capsule container	7
2.4	PTS current allocation applications	8
2.5	The carrier mail	9
2.6	Daryl Oster's projects of evacuated tube transport	9
2.7	PCPs used in Japan (a) circular section, and (b) rectangular section	10
2.8	PCP used in Japan (a) conduit with semi-circular cross section (b) the capsule	11
2.9	Fully developed flow in a pipe	15
2.10	Pitot tube inserted with a cross section of pipe	15
2.11	Digital Pitot tube tool with pressure reading	16
2.12	FX63-137 airfoil profile	22
2.13	Lift versus drag coefficient of FX63-137 at $Re = 100,000$	23
2.14	Lift coefficient of FX63-137 at $Re = 100,000$	23
2.15	Moment coefficient of FX63-137 at $Re = 100,000$	24
2.16	NACA 0012 airfoil profile	25
2.17	Lift versus drag coefficient of NACA0012 at $Re = 100,000$	25
2.18	Lift coefficient of NACA0012 at $Re = 100,000$	26
2.19	Moment coefficient of NACA0012 at $Re = 100,000$	26
2.20	NACA 4412 airfoil profile	27

2.21	Lift versus drag coefficient of NACA4412 at $Re = 100,000$	27
2.22	Lift coefficient of NACA4412 at $Re = 100,000$	28
2.23	Moment coefficient of NACA4412 at $Re = 100,000$	28
2.24	Span dominated ground effect	31
3.1	The CFD methodology	44
3.2	The Overview of the CFD	44
3.3	Three-dimensional design of (a) Box, (b) Ball, (c) Wedge A and (d) Wedge B shapes	45
3.4	Three-dimensional view of the air tunnels and models (a) Box, (b) Ball, (c) Wedge A, and (d) Wedge B	47
3.5	Models (a) for a box, (b) for the wing, and (c) for the carrier	48
3.6	Three-dimensional view of the air tunnel and the carrier	48
3.7	The air tunnel (a) YZ plane, and (b) XY plane	49
3.8	The scaled-up box with rectangular-shaped wings attached	49
3.9	Wings with rectangular shape for (a) FX63-137 airfoil, (b) NACA 0012 airfoil, and (c) NACA 4412 airfoil	50
3.10	Three-dimensional view of the air tunnel and the carrier	50
3.11	The air tunnel (a) YZ plane, and (b) XY plane	51
3.12	The wedge B with rectangular-shaped wings attached (NACA0012)	51
3.13	Wing in rectangular shape for NACA 0012 airfoil	51
3.14	Three-dimensional view of the air tunnel and the wedge B	52

3.15	The air tunnel and wedge B for (a) YZ plane, and (b) XY plane	52
3.16	The boundary conditions of the 3D view of the air tunnel and the carrier	53
3.17	Shows the boundary conditions of the 3D view of the air tunnel and the wedge B	54
3.18	Shows the boundary condition of three-dimensional view of the air tunnels and the carriers, (a) Box, (b) Ball, (c) Wedge A, and (d) Wedge B	54
3.19	Grid distribution for three dimensional flow problem for (a) Box, (b) Ball, (c) Wedge A, and (d) Wedge B	55
3.20	Tetrahedral meshes around the model	56
3.21	Grid section of the mesh of the carrier and circular cross-section of air tunnel of (a) FX63-137 airfoil, (b) NACA 0012 airfoil, and (c) NACA 4412 airfoil	56
3.22	Grid section of the mesh for a circular cross-section of the air tunnel, the wedge B, and around the wing (NACA0012)	57
3.23	The domain of testing carriers (FX63-137), (NACA0012), and (NACA4412)	58
3.24	The grid mesh for carriers (FX63-137), (NACA0012), and (NACA4412)	58
3.25	The air tunnel and the blower pump	61
3.26	The flow chart of the experimental setup	61
3.27	Air tunnel from inside view	62
3.28	Metallic filter	62
3.29	Blower pump	63
3.30	The real carriers (a) Carrier (FX63-137), (b) Carrier (NACA0012, and, (c) Carrier (NACA4412)	64
3.31	The location of the carrier inside the air tunnel	64

3.32	Nikon 1 J1 camera	65
3.33	Shows the flow chart of experiment procedure	66
3.34 (a)	The real air tunnel and the position of the carrier	67
3.34 (b)	The source of the air (blower pump) and the linked pipes (air tunnel)	67
3.35	The removable door and the small converter pipe	67
4.1	Comparison of velocity magnitude for 3D mesh (a) Box, (b) Ball, (c) Wedge A, and (d) Wedge B	70
4.2	Comparison of X-component velocities of the box, ball, wedge A and wedge B shapes	73
4.3	Velocity contours of the flow field around the 3D models located in the middle of air tunnel, XY-plane	74
4.4	Velocity contours of the flow field around the 3D models located in the middle of air tunnel, YZ-plane	75
4.5	Pressure contours of the flow field around the 3D models located in the middle of air tunnel, XY-plane	76
4.6	Pressure contours of the flow field around the 3D models located in the middle of air tunnel, YZ-plane	77
4.7	Distance traveled by the carrier (a) the motion in X-direction, (b) the motion in Y-direction, and (c) the motion in Z-direction	79
4.8	Velocity of the carrier with respect to time	80
4.9	Velocity contours of the flow field around the carrier at each time instant (Front view)	81
4.10	Velocity contours of the flow field around the carrier at each time instant (Side view)	82
4.11	Pressure contours of the flow field around the carrier at each time instant (Front view)	84
4.12	Pressure contours of the flow-field around the	85

	carrier at each time instant (Side view)	
4.13	Carrier trajectory	87
4.14	Distance traveled by the carriers (a) the motion in X-direction, (b) the motion in Y-direction, and (c) the motion in Z-direction	88
4.15	Velocity components for the carriers with respect to time	90
4.16	Pressure and velocity contours of the flow field around the carrier (FX63-137) in YZ-plane	91
4.17	Pressure and velocity contours of the flow field around the carrier (FX63-137) in XY-plane	92
4.18	Pressure and velocity contours of the flow field around the carrier (NACA4412) in YZ-plane	94
4.19	Pressure and velocity contours of the flow field around the carrier (NACA4412) in XY-plane	96
4.20	Pressure and velocity contours of the flow field around the carrier (NACA0012) in YZ-plane	97
4.21	Pressure and velocity contours of the flow field around the carrier (NACA0012) in XY-plane	99
4.22	Carriers trajectory	101
4.23	Carrier (FX63-137) trajectory	103
4.24	Carrier (NACA0012) trajectory	103
4.25	Carrier (NACA4412) trajectory	104
4.26	Trajectory of wedge B (NACA0012) for different weights	105
4.27	Trajectory of carrier (NACA0012) for different weights	106
4.28	Trajectory of wedge B (NACA0012) and the carrier (NACA0012) for the weight of 100 grams	107
4.29	Trajectory of wedge B (NACA0012) and the carrier (NACA0012) for the weight of 200 grams	108
4.30	Trajectory of wedge B (NACA0012) and the	110



	carrier (NACA0012) for the weight of 300 grams	
4.31	Trajectory of wedge B (NACA0012) and the carrier (NACA0012) for the weight of 400 grams	112
4.32	Trajectory of wedge B (NACA0012) and the carrier (NACA0012) for the weight of 500 grams	113
5.1	Experiment results for the carrier (FX63-137) captured by high speed camera	116
5.2	Pressure contours of the flow field around the carrier (FX63-137) in various positions for XY-plane	121
5.3	Velocity contours of the flow field around the carrier (FX63-137) in various positions for XY-plane	123
5.4	Distance traveled by the carrier in the X-direction versus velocity magnitude ( $u$ )	126
5.5	Velocity magnitude ( $u$ ) of the carrier with respect to time	126
5.6	Distance traveled by the carrier in the X-direction versus the time taken to experiment and numerical results	127
5.7	Carrier (FX63-137) trajectory	127
5.8	Pressure contours of the flow field around the carrier (FX63-137) in various positions for YZ-plane	128
5.9	Velocity contours of the flow field around the carrier (FX63-137) in various positions for YZ-plane	130
5.10	Pitching moment variation with incidence angles for a stable carrier (FX63-137)	133
5.11	Lift coefficient $C_l$ versus angle of attack for carrier (FX63-137)	133
5.12	Drag coefficient $C_d$ versus angle of attack for carrier (FX63-137)	134

5.13	Lift coefficient $C_l$ versus the drag coefficient $C_d$ for carrier (FX63-137)	134
5.14	Experiment results for the carrier (NACA 0012) captured by high-speed camera	135
5.15	Pressure contours of the flow field around the carrier (NACA0012) in various positions for XY-plane	139
5.16	Velocity contours of the flow field around the carrier (NACA0012) in various positions for XY-plane	141
5.17	The distance traveled by the carrier in the X-direction versus velocity magnitude ( $u$ )	143
5.18	Velocity magnitude ( $u$ ) of the carrier with respect to time	144
5.19	The distance traveled by the carrier (NACA0012) in the X-direction versus the time taken to experiment and numerical results	144
5.20	Carrier (NACA0012) trajectory	145
5.21	Pressure contours of the flow field around the carrier (NACA0012) in various positions for YZ-plane	146
5.22	Velocity contours of the flow field around the carrier (NACA0012) in various positions for YZ-plane	147
5.23	Pitching moment variation with incidence angles for a stable carrier (NACA0012)	149
5.24	Lift coefficient $C_l$ versus angle of attack for carrier (NACA0012)	149
5.25	Drag coefficient $C_d$ versus angle of attack for carrier (NACA0012)	150
5.26	Lift coefficient $C_l$ versus the drag coefficient $C_d$ for carrier (NACA0012)	150
5.27	Experiment results for the carrier (NACA 4412)	151

	captured by high-speed camera	
5.28	Pressure contours of the flow field around the carrier (NACA4412) in various positions for XY-plane	156
5.29	Velocity contours of the flow field around the carrier (NACA4412) in various positions for XY-plane	158
5.30	The distance traveled by the carrier in the X-direction versus velocity magnitude ( $u$ )	160
5.31	Velocity magnitude ( $u$ ) of the carrier with respect to time	160
5.32	The distance traveled by the carrier (NACA4412) in the X-direction versus the time taken to experiment and numerical results	161
5.33	Carrier (NACA4412) trajectory	161
5.34	Pressure contours of the flow field around the carrier (NACA4412) in various positions for YZ-plane	163
5.35	Velocity contours of the flow field around the carrier (NACA4412) in various positions for YZ-plane	164
5.36	Pitching moment variation with incidence angles for a stable carrier (NACA4412)	166
5.37	Lift coefficient $C_l$ versus angle of attack for carrier (NACA4412)	166
5.38	Drag coefficient $C_d$ versus angle of attack for carrier (NACA4412)	167
5.39	Lift coefficient $C_l$ versus the drag coefficient $C_d$ for carrier (NACA4412)	167

## LIST OF SYMBOLS AND ABBREVIATIONS

2D	-	Two-dimensional
3D	-	Three-dimensional
$\alpha$	-	Angle of attack
$\alpha_{trim}$	-	Trim angle
$C_m$	-	Pitching moment coefficient
$C_l$	-	Lift coefficient
$C_d$	-	Drag coefficient
$M$	-	Pitching moment
$L$	-	Lift force
$D$	-	Drag force
$c$	-	Chord length
$A$	-	Wing area
$S$	-	Full area of the carrier
$u$	-	The velocity in X-direction
$v$	-	The velocity in Y-direction
$w$	-	The velocity in Z-direction
$v$	-	Flow velocity
$\gamma$	-	Specific weight
$g$	-	Acceleration of gravity
$h$	-	Elevation height
$\rho$	-	Density
$F$	-	Force
N	-	Newton
ms	-	Millisecond
Hz	-	Hertz
$\mu$	-	Molecular viscosity
$\Delta$	-	Vector operator

$\bar{p}$	-	Time-averaged pressure
$p$	-	Static pressure
$\bar{u}, \bar{v}, \bar{w}$	-	Time-averaged velocity components
$u', v', w'$	-	Fluctuating velocity components
$v_x, v_y, v_z$	-	Velocity components
$v_c$	-	Total velocity
$u_i$	-	Instantaneous velocity
$U_i$	-	Mean velocity
$\tau_{ij}$	-	Reynolds stress tensors
$\mu_T$	-	eddy viscosity
$k$	-	Turbulent kinetic energy
$\varepsilon$	-	Dissipation rate
$\Omega$	-	specific dissipation rate
$\partial$	-	Partial derivative
Pa	-	Pascal, $N/m^2$
T	-	Time
M	-	Meter
S	-	Second
min	-	Minute
V15	-	Version 2015
V16.1	-	Version 2016
UTHM	-	Universiti Tun Hussein Onn Malaysia
Fps	-	Frame per second
CPU	-	Central Processing Unit
SDOF	-	Six degree of freedom
RANS	-	Reynolds Averaged Navier-Stokes
PDEs	-	Partial Differential Equations
CFD	-	Computational Fluid Dynamic
EMS	-	Electromagnetic Suspension
EDS	-	Electrodynamic Suspension
HEMS	-	Hybrid Electromagnetic Suspension

PMG	-	Postmaster General
Maglev	-	Magnetic levitation
WIG	-	Wing-In-Ground
DGE	-	Dynamic Ground Effect
PCP	-	Pneumatic Capsule Pipeline
PTC	-	Pneumatic Tube Capsule
PTS	-	Pneumatic Tube Systems
GmbH	-	Gesellschaft mit beschränkter Haftung (company with limited liability)
HMSO	-	Her Majesty's Stationery Office
FVM	-	Finite Volume Method
SIMPLE	-	Semi-Implicit Method for Pressure-Linked Equations
NACA	-	National Advisory Committee for Aeronautics
PLA	-	Polylactic Acid
PIV	-	Particle Image Velocimetry
DGE	-	Dynamic Ground Effect



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	FX 63-137 13.7% smoothed - Wortmann FX 63-137 airfoil data	181
B	NACA 0012 airfoil data	182
C	NACA 4412 airfoil data	184
D	The lift and the drag forces and the torque acted on the carrier (FX63-137) at each time step for pressure difference is 1600 Pa	186
E	The lift and the drag forces and the torque acted on the carrier (FX63-137) at each time step for pressure difference is 700 Pa	187
F	Carrier (FX63-137)	189
G	The lift and the drag forces and the torque acted on the carrier (FX63-137) at each time step for pressure difference is 235 Pa	191
H	NACA(0012)	192
I	The lift and the drag forces and the torque acted on the carrier (NACA0012) at each time step for pressure difference is 235 Pa	194
J	NACA(4412)	195
K	The lift and the drag forces and the torque acted on the carrier (NACA4412) at each time step for pressure difference is 235 Pa	197

## LIST OF PUBLICATIONS

### A. Journal papers:

1. Shibani, E., Zulkafli, M. F., Basuno, B., & Ab Wahab, A. B. (2016). Numerical Analysis of a Moving Object in the Air Tunnel. *International Journal of Mechanical & Mechatronics Engineering IJMME*, 16, 72-8.

### B. Conference papers:

1. Shibani, W. M., Zulkafli, M. F., & Basuno, B. (2016, November). Numerical Study of a Winged Container Moving in an Air Tunnel. In *IOP Conference Series: Materials Science and Engineering* (Vol. 160, No. 1, p. 012041). IOP Publishing.
2. Shibani, W. M., Zulkafli, M. F., & Basuno, B. (2016, November). Methods of Transport Technologies: A Review on Using Tube/Tunnel Systems. In *IOP Conference Series: Materials Science and Engineering* (Vol. 160, No. 1, p. 012042). IOP Publishing.
3. Shibani, W. M. E., Zulkafli, M. F., & Basuno, B. (2017, April). A comparative study on the motion of various objects inside an air tunnel. In *AIP Conference Proceedings* (Vol. 1831, No. 1, p. 020005). AIP Publishing.
4. Saad, M. M. M., Mohd, S. B., Zulkafli, M. F., & Shibani, W. M. E. (2017, April). Numerical analysis for comparison of aerodynamic characteristics of six airfoils. In *AIP Conference Proceedings* (Vol. 1831, No. 1, p. 020004). AIP Publishing.
5. Shibani, W. M., Zulkafli, M. F., Basuno, B., Ghafir, M. A., & Subari, Z. (2017, September). Experimental and numerical simulation of a moving carrier (FX63-137) through an air tunnel. In *IOP Conference Series:*



## REFERENCES

- Ahmed, M. R., & Sharma, S. (2005). An investigation on the aerodynamics of a symmetrical airfoil in ground effect. *Experimental Thermal and Fluid Science*, 29(6), 633-647.
- Al-Kayiem, H. H., & Bruun, H. (1991). Evaluation of a flying X hot-wire probe system. *Measurement Science and Technology*, 2(4), 374.
- Albicini, F., Andriollo, M., Martinelli, G., & Morini, A. (1993). General expressions of propulsion force in EDS-MAGLEY transport systems with superconducting coils. *IEEE Transactions on Applied Superconductivity*, 3(1), 425-429.
- Aldhous, P., Anderson, A., Coghlan, A., Mullins, J., O'Neill, B., & Spinney, L. (1995). Beneath your feet. *New Scientist*, 146(5).
- Anderson, J. D., & Wendt, J. (1995). Computational fluid dynamics (Vol. 206). In: Springer.
- Asim, T., & Mishra, R. (2016). Computational fluid dynamics based optimal design of hydraulic capsule pipelines transporting cylindrical capsules. *Powder Technology*, 295, 180-201.
- Asim, T., Mishra, R., Paris, A., & Zala, K. (2013). Optimal Design Methodology for On-shore Hydraulic Pipelines Transporting Spherical Capsules. *Procedia CIRP*, 11, 305-310.
- Asselin, M. (1997). *An introduction to aircraft performance*: AIAA.
- Badran, O. (1993). *A flying hot-wire study of separated flows*. Ph. D. thesis. Department of Mechanical and Manufacturing Engineering, University of Bradford,
- Badran, O., & Bruun, H. (2003). Turbulent flow over a NACA 4412 airfoil at angle of attack 15 degree. *Paper presented at the ASME/JSME 2003 4th Joint Fluids Summer Engineering Conference*.

- Barber, T. (2006). Aerodynamic ground effect: a case study of the integration of CFD and experiments. *International Journal of Vehicle Design*, 40(4), 299-316.
- Beach, A. (1870). The pneumatic tunnel under Broadway. *New York Scientific American*, 22, 154-156.
- Belova, O., & Vulf, M. (2016). Pneumatic capsule transport. *Procedia Engineering*, 152, 276-280.
- Brown, G. (2001a). Henry Darcy and the Pitot tube. In *International Engineering History and Heritage: Improving Bridges to ASCE's 150th Anniversary* (pp. 360-366).
- Brown, G. (2001b). Henry Darcy and the Pitot tube. *International Engineering History and Heritage*, (pp. 360-366).
- Button, K. J., & Pearman, A. D. (1981). *The economics of urban freight transport* (1st ed.). London and Basingstoke: Springer.
- Chou, P. Y. (1945). On velocity correlations and the solutions of the equations of turbulent fluctuation. *Quarterly of Applied Mathematics*, 3(1), 38-54.
- Cohen, R. A. (1999). The Pneumatic Mail Tubes: New York's Hidden Highway And Its Development. *Paper presented at the Proceedings of the 1st International Symposium on Underground Freight Transport by Capsule Pipelines and Other Tube/Tunnel Systems, Columbia, Missouri.*
- Cui, E., & Zhang, X. (2010). Ground effect aerodynamics. *Encyclopedia of Aerospace Engineering*.
- Davey, K. R. (1997). Electrodynamic Maglev coil design and analysis. *IEEE Transactions on Magnetics*, 33(5), 4227-4229.
- David, B. (1995). *Transport and urban development* (First ed.): Taylor & Francis.
- Davidov, B. (1961). On statistical dynamics of an incompressible turbulent flow. *Soviet Phys. Dokl*, 6, 10-12.
- Divitiis, N. D. (2005). Performance and stability of a winged vehicle in ground effect. *Journal of Aircraft*, 42(1), 148-157.
- Eastham, A., & Hayes, W. (1988). Maglev systems development status. *IEEE Aerospace and Electronic Systems Magazine*, 3(1), 21-30.
- Eleni, D. C., Athanasios, T. I., & Dionissios, M. P. (2012). Evaluation of the turbulence models for the simulation of the flow over a National Advisory

- Committee for Aeronautics (NACA) 0012 airfoil. *Journal of Mechanical Engineering Research*, 4(3), 100-111.
- Firooz, A., & Gadami, M. (2006). Turbulence flow for NACA 4412 in unbounded flow and ground effect with different turbulence models and two ground conditions: fixed and moving ground conditions. *Paper presented at the Conference on Boundary and Interior Layers*.
- Fluent, A. (2015). Ansys fluent. *Academic Research. Release*, 14.
- FX63-137. (2017). FX63-137 Airfoil data. (Accessed on 19 October, 2017). Retrieved from <http://airfoiltools.com/polar/details?polar=xf-fx63137sm-il-100000>
- Galilei, G. (1954). *Dialogues Concerning Two New Sciences: Galileo Galilei*: Dover.
- GMBH. (2015). Ing. Sumetzberger (Accessed on August 31 2016). Retrieved from <https://www.sumetzberger.at/en/home>.
- Gosman, A. (1999). Developments in CFD for industrial and environmental applications in wind engineering. *Journal of Wind Engineering and Industrial Aerodynamics*, 81(1), 21-39.
- Hackborn, W. (2006). Motion through air: what a drag. *Can. Appl. Math. Quart*, 14, 285-298.
- Hardy, G. H., & Snow, C. P. (1967). *A Mathematicians's Apology, with a Foreward by CP Snow*: CUP.
- Harlow, F. H., & Nakayama, P. I. (1968). *Transport of turbulence energy decay rate*. Retrieved from
- Hensher, D. A. (1977). *Urban transport economics*: CUP Archive.
- HMSO. (2013). *Health Technical Memorandum, 2009*. London.
- Hogan, J., & Fink, H. (1975). Comparison and optimization of lift and drag forces on vehicles levitated by eddy current repulsion for various null and normal flux magnets with one or two tracks. *IEEE Transactions on Magnetics*, 11(2), 604-607.
- Hossain, A., Rahman, A., Iqbal, A., Ariffin, M., & Mazian, M. (2012). Drag analysis of an aircraft wing model with and without bird feather like winglet. *International Journal of Aerospace and Mechanical Engineering*, 6(1), 8-13.

- Hossain, M. S., Raiyan, M. F., Akanda, M. N. U., & Jony, N. H. (2014). A Comparative flow analysis of NACA 6409 and NACA 4412 aerofoil. *International Journal of Research in Engineering and Technology*, 3.
- Howgego, T., & Roe, M. (1998). The use of pipelines for the urban distribution of goods. *Transport Policy*, 5(2), 61-72.
- Hua, X., Zhang, C., Zhang, G., Wang, P., & Zhao, X. (2012). High altitude and long endurance unmanned aerial vehicle bionic airfoil research. *Paper presented at the 2012 4th Electronic System-Integration Technology Conference*.
- Hyperloop (2016). (Accessed on 18 September, 2016). Retrieved from <http://hyperlooptech.com/>
- Jacobs, E. N., Ward, K. E., & Pinkerton, R. M. (1933). The characteristics of 78 related airfoil sections from tests in the variable-density wind tunnel. *NASA Technical Reports server (NTRS)* (Jan 01, 1933 ), 61p.
- Jayawant, B. V. (1981). *Electromagnetic levitation and suspension techniques*. 41 Bedford Square, London, United Kingdom Edward Arnold Publishers Limited
- Jones, W., & Launder, B. (1972). The prediction of laminarization with a two-equation model of turbulence. *International Journal of Heat and Mass Transfer*, 15(2), 301-314.
- Jvarsheishvili, A. (1981). Pneumo-capsule pipelines in USSR. *Elsevier Science*, 1, 109-110. Amsterdam, Netherlands.
- Kandwal, S., & Singh, S. (2012). Computational fluid dynamics study of fluid flow and aerodynamic forces on an airfoil. *Paper presented at the International Journal of Engineering Research and Technology*.
- Kanyako, F., & Janajreh, I. (2013). Investigating blade performance of small horizontal axis wind turbine based on blade element momentum theory. *Paper presented at the 2013 1st International Conference & Exhibition on the Applications of Information Technology to Renewable Energy Processes and Systems (IT-DREPS)*
- Keshgegian, A. A., & Bull, G. E. (1992). Evaluation of a soft-handling computerized pneumatic tube specimen delivery system: effects on analytical results and turnaround time. *American Journal of Clinical Pathology*, 97(4), 535-540.

- Kim, D.-H., Lee, J.-K., Hahn, S.-Y., & Cha, G. (1996). New levitation scheme with AC superconducting magnet for EDS MAGLEV system. *IEEE Transactions on Magnetics*, 32(5), 5151-5153.
- Kosugi, S. (1992). A capsule pipeline system for limestone transportation. *Paper presented at the 4th International Conference on Bulk Materials, Storage, Handling and Transportation: 7th International Symposium on Freight Pipelines; Preprints of Papers*.
- Kosugi, S. (1999a). Effect of traveling resistance factor on pneumatic capsule pipeline system. *Powder Technology*, 104(3), 227-232.
- Kosugi, S. (1999b). *Pneumatic capsule pipelines in Japan and future developments*.
- Kosugi, S., Fukunaga, T., Matsui, N., Saito, K., Hane, K., & Okutsu, K. (2003). Applicability of Pneumatic Capsule Pipeline to Radioactive Waste Disposal Facility. In *New Pipeline Technologies, Security, and Safety* (pp. 1615-1624).
- Launder, B., & Sharma, B. (1974). Application of the energy-dissipation model of turbulence to the calculation of flow near a spinning disc. *Letters in heat and mass transfer*, 1(2), 131-137.
- Lee, H.-W., Kim, K.-C., & Lee, J. (2006). Review of maglev train technologies. *IEEE Transactions on Magnetics*, 42(7), 1917-1925.
- Leephakpreeda, T. (2009). Novel method to weigh medical capsules in continuous process. *Measurement*, 42(7), 1053-1058.
- Leishman, G. J. (2006). *Principles of helicopter aerodynamics* (Second ed.). United State of America: Cambridge university press.
- Leonard III, N. J. (2001). *Wing in Ground Effect Aircraft: An Airlifter of the Future*. Retrieved from
- Littlewood, J. (1971a). Adventures in ballistics I, II, Math. *Spectrum*, 4, 31-38.
- Littlewood, J. (1971b). Adventures in ballistics, 1915-1918, II, Math. *Spectrum*, 4, 80-86.
- Liu, H. (2000). Pneumatic Capsule Pipeline Basic Concept, Practical Considerations, and Current Research. *Paper presented at the Proceedings of Mid-Continent Transportation Symposium*.
- Liu, H. (2004). Feasibility of Using Pneumatic Capsule Pipelines in New York City for Underground Freight Transport. In *Pipeline Engineering and Construction: What's on the Horizon?* (pp. 1-12).

- Liu, H. (2006). Transporting freight containers by pneumatic capsule pipeline (PCP): port security and other issues. *Paper presented at the Invited presentation at Summer Meeting of US Transportation Research Board (TRB) LaJolla, California.*
- Lynam, D. (1978). *The Development of a Cost Model for Pneumatic Capsule Pipeline Systems*. Pneumotransport 4. British Hydro Dynamics Research Association.
- Marcus, R. (2012). *Pneumatic conveying of solids*: Springer Science & Business Media.
- Masatsuka, K. (2013). *I do Like CFD, vol. 1* (Vol. 1): Lulu. com.
- Mashud, M., Ferdous, M., & Ome, S. H. (2012). Effect of spoiler position on aerodynamic characteristics of an airfoil. *International Journal of Mechanical and Mechatronics Engineering, Bangladesh*, 12(6).
- Massey, B. S., & Ward-Smith, J. (1998). *Mechanics of fluids* (Vol. 1): CRC Press.
- Middha, P., Balakin, B. V., Leirvaag, L., Hoffmann, A. C., & Kosinski, P. (2013). PEPT—A novel tool for investigation of pneumatic conveying. *Powder Technology*, 237, 87-96.
- Mohammad Sadraey. (Wing Design. (Accessed on 10-10-2016,2016). Retrieved from [faculty.dwc.edu/sadraey/Chapter%205.%20Wing%20Design.pdf](http://faculty.dwc.edu/sadraey/Chapter%205.%20Wing%20Design.pdf)
- NACA0012. (2016).UIUC Applied Aerodynamics Group (Accessed on 10 October,2016). Retrieved from [http://m-selig.ae.illinois.edu/ads/coord\\_database.html#N](http://m-selig.ae.illinois.edu/ads/coord_database.html#N)
- NACA0012. (2017).NACA0012 Airfoil data. (Accessed on 19 October,2017). Retrieved from <http://airfoiltools.com/polar/details?polar=xf-n0012-il-100000>
- NACA4412. (2016).UIUC Applied Aerodynamics Group (Accessed on 10 October,2016). Retrieved from [http://m-selig.ae.illinois.edu/ads/coord\\_database.html#N](http://m-selig.ae.illinois.edu/ads/coord_database.html#N)
- NACA4412. (2017).NACA4412 Airfoil data. (Accessed on 19 October,2017). Retrieved from <http://airfoiltools.com/polar/details?polar=xf-naca4412-il-100000>
- Nakayama, A. (1985). Characteristics of the flow around conventional and supercritical airfoils. *Journal of Fluid Mechanics*, 160, 155-179. Newton, R., Redberger, P., & Round, G. (1963). Numerical analysis of some variables determining free flow. *Can. J. Chem. Eng.*, 42, 168-173.



- Norberg, C., Sohankar, A., & Davidson, L. (1995). Numerical simulation of unsteady flow around a square two-dimensional cylinder. *Paper presented at the Twelfth Australian Fluid Mechanics Conference.*
- Ogden, K. W. (1992). *Urban goods movement: a guide to policy and planning.* 119 Cherry Street, Suite 3-1, Burlington, VT USA 05401-3818: Ashgate Publishing Company.
- Ohmi, K., Coutanceau, M., Daube, O., & Loc, T. P. (1991). Further experiments on vortex formation around an oscillating and translating airfoil at large incidences. *Journal of Fluid Mechanics*, 225, 607-630.
- Onuki, T., & Toda, Y. (1993). Optimal design of hybrid magnet in maglev system with both permanent and electromagnets. *IEEE Transactions on Magnetics*, 29(2), 1783-1786.
- Oster, D. (1999). Evacuated tube transport. In: Google Patents.
- Peggs, L. A. (1985). *Underground piping handbook.* Robert E. Krieger Publishing Company Inc., Melbourne, FL(1985-01-01).
- Pinkerton, R. M. (1938). The variation with Reynolds number of pressure distribution over an airfoil section. *NASA Technical Reports server (NTRS)* (Jan 01, 1938 ), 20p.
- Qu, Q., Jia, X., Wang, W., Liu, P., & Agarwal, R. K. (2014). Numerical study of the aerodynamics of a NACA 4412 airfoil in dynamic ground effect. *aerospace Science and Technology*, 38, 56-63.
- Raffel, M., Kompenhans, J., & Wernert, P. (1995). Investigation of the unsteady flow velocity field above an airfoil pitching under deep dynamic stall conditions. *Experiments in Fluids*, 19(2), 103-111.
- Riches, E. (1988). Will maglev lift off? *IEE Review*, 34(11), 427-430.
- Rogg, D. (1984). General survey of the possible applications and development tendencies of magnetic levitation technology. *IEEE Transactions on Magnetics*, 20(5), 1696-1701.
- Rote, D. M., & Cai, Y. (2002). Review of dynamic stability of repulsive-force maglev suspension systems. *IEEE Transactions on Magnetics*, 38(2), 1383-1390.
- Roudier, J. (1976). Freight Collection and Delivery in Urban Areas: Report of the Thirty-first Round Table on Transport Economics Held in Paris on 20th and 21st November 1975.

- Sakamoto, T., & Shiromizu, T. (1997). Propulsion control of superconducting linear synchronous motor vehicle. *IEEE Transactions on Magnetics*, 33(5), 3460-3462.
- Schmid, S., Lutz, T., & Krämer, E. (2009). Impact of Modelling Approaches on the Prediction of Ground Effect Aerodynamics. *Engineering Applications of Computational Fluid Mechanics*, 3(3), 419-429.
- Selig, M., & McGranahan, B. (2004). Wind tunnel aerodynamic tests of six airfoils for use on small wind turbines. *Paper presented at the 42nd AIAA Aerospace Sciences Meeting and Exhibit*.
- Sen, P. (1975). On linear synchronous motor (LSM) for high speed propulsion. *IEEE Transactions on Magnetics*, 11(5), 1484-1486.
- Sherwin, K. (1975). *Man-powered flight*: Model and Allied Pub.
- Sinha, P. (1984). Design of a magnetically levitated vehicle. *IEEE Transactions on Magnetics*, 20(5), 1672-1674.
- Swisslog. (2014). Pneumatic Tube Systems Intelligent Solutions for Hospital. *Swisslog Rohrpostsysteme GmbH*. Germany.
- Tanley, P., Wallas, C., Abram, M., & Richardson, L. D. (1987). Use of a pneumatic tube system for delivery of blood bank products and specimens. *Transfusion*, 27(2), 196-198.
- Tannehill, J. C., Anderson, D. A., & Pletcher, R. H. (1997). Computational fluid mechanics and heat transfer, Series in computational and physical processes in mechanics and thermal sciences. In: Taylor & Francis, Washington, DC.
- Tao, W.-Q. (2001). Numerical heat transfer. In: Xi'an Jiaotong University Press, Xi'an.
- Van den Kroonenberg, H. (1979). A mathematical model for concentric horizontal capsule transport. *The Canadian Journal of Chemical Engineering*, 57(3), 383-383.
- Vance, L., & Mattson, P. (1994). Tube transportation. *US Dept of Transportation, Volpe National Transportation Systems Center, Feb*.
- Versteeg, H. K., & Malalasekera, W. (2007). *An introduction to computational fluid dynamics: the finite volume method*: Pearson Education.
- Wadcock, A. J. (1978). *Flying-hot-wire study of two-dimensional turbulent separation of an NACA 4412 airfoil at maximum lift*. California Institute of Technology,



- Wang, T. C., & Tzeng, Y.-k. (1994). A new electromagnetic levitation system for rapid transit and high speed transportation. *IEEE Transactions on Magnetics*, 30(6), 4734-4736.
- Weh, H., & Shalaby, M. (1977). Magnetic levitation with controlled permanentic excitation. *IEEE Transactions on Magnetics*, 13(5), 1409-1411.
- White, F. M. (2003). Fluid Mechanics,(2003). Chap, 5(New York, USA), p287.
- Wortmann. (2016).UIUC Applied Aerodynamics Group (Accessed on 10 October 2016). Retrieved from [http://m-selig.ae.illinois.edu/ads/coord\\_database.html#N](http://m-selig.ae.illinois.edu/ads/coord_database.html#N)
- Wortmann. (2017).FX63-137 airfoil. (Accessed on 19 October,2017). Retrieved from <http://airfoiltools.com/polar/details?polar=xf-fx63137sm-il-100000>
- Yamamura, S. (1976). Magnetic levitation technology of tracked vehicles present status and prospects. *IEEE Transactions on Magnetics*, 12(6), 874-878.
- Zandi, I. (1978). A comparative study of pneumo-capsule pipeline, truck and rail for transport of manufactured cargo, Pneumotransport 4. California, BHRA.
- Zhang, X., Wang, S., & Yu, D. (2009). 2D axisymmetric CFD simulation of underwater torpedo launch tube flow. *Paper presented at the International Conference on Information Engineering and Computer Science, 2009. ICIECS 2009.*
- Zhou, H., Cui, G., Xu, C., & Zhang, Z. (2003). Thin layer structure of dissipation rate of scalar turbulence. *Science in China Series E: Technological Sciences*, 46(2), 209-217.